



## C2422E HYPERCELL

HPL 4.3-10 male elbow connector

## GENERAL CHARACTERISTICS

Inner Conductor:	Silver - plated bronze
Dielectric:	PTFE
Body:	Copper alloy - plated brass
Clamping and Coupling Nut:	Nickel - plated brass
Clamping Nut Waterproof:	Silicone O-ring
Coupling Waterproof:	Silicone O-ring

## MECHANICAL & ENVIRONMENTAL

Interface Durability:	>100 cycles	
Temperature:	Operating	-40°C / +85°C
	Installation	-25°C / +55°C
	Storage	-50°C / +85°C
Weight:	257 g	
Waterproof Index:	IP68	
RoHS Compliance:	Yes	

## ELECTRICAL

Impedance:	50 ± 1 Ω
Operating Frequency Band:	DC ~ 4 GHz
VSWR:	DC ~ 2.2 GHz: ≤ 1.10
	2.2 ~ 3 GHz: ≤ 1.135
	3 ~ 4 GHz: ≤ 1.20
3rd Order Passive Intermodulation, Measured In Swept Frequency Mode with 2x20W carriers, F ≤ 1880 MHz:	≤ -160 dBc
Voltage Test (at sea level):	2000 V eff / 50 Hz
Operating Voltage (at sea level):	1400 V eff / 50 Hz
Insulation Resistance:	≥ 5000 MΩ
Contact Resistance:	Inner contact: ≤ 1.0 mΩ
	Outer contact: ≤ 1.0 mΩ

## RANGE

Compatibility with ACOME HPL 50 50 -7/8

M5407, M5422, M5510,M5430,M5436,M5643,M5645

Test Methods: IEC 61169-54, IEC 62037-3, IEC 60529

## RECOMMENDATIONS

### INSTALLATION INSTRUCTION

ANM – C2422E