

C0025E HYPERCELL

Jumper 1/2SF PE N Male – N Male

GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF PE cable
Connector:	N male
Assembly:	Inner and outer contact 100% soldered and with molding

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	2.5 N.m Max.
Minimum Bending Radius:	25 mm

ENVIRONMENTAL

Operating Temperature Range:	-55°C < θ < + 70°C
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

ELECTRICAL

Impedance:		50 ± 1Ω		
Operating Frequency Range:		DC ~ 3GHz		
RMS Power (40 °C - 2 GHz):		0.52 KW		
Velocity:		83%		
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	≤ -160 dBc		
	IM3 at 1800MHz	≤ -160 dBc	IM7 at 2100MHz	≤ -160 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
0.2	C0992E	160	-32	0.15	-30	0.22	-26	0.25
0.5	C0704E	217	-32	0.17	-30	0.26	-26	0.31
1	C0024E	300	-32	0.21	-30	0.33	-26	0.37
1.5	C0025E	390	-32	0.26	-30	0.40	-26	0.47
2	C0026E	480	-32	0.33	-30	0.48	-26	0.57
2.5	C0027E	560	-32	0.38	-30	0.57	-26	0.67
3	C0028E	650	-32	0.43	-30	0.66	-26	0.78
4	C1453E	830	-32	0.56	-30	0.86	-26	1.01
5	C0930E	1000	-32	0.66	-30	1.03	-26	1.22
6	C1419E	1170	-32	0.78	-30	1.19	-26	1.42
10	C1437E	1850	-30	1.22	-28	1.84	-24	2.19