



## **C0867E**

### **HYPERCELL**

Jumper 1/2SF PE 7/16 Din Male - N Female

# GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF PE cable
Connector:	7/16 Din male / N female
Assembly:	Inner and outer contact 100% soldered and with molding

## MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass		
Material and Finish of Coupling Nut:	Nickel - plated brass		
Material and Finish of Inner Conductor:	Silver - plated bronze		
Coupling Waterproof:	Silicone Rubber O-ring		
Coupling Torque:	N interface	2.5 N.m Max.	
	Din interface	30 N.m Max.	
Minimum Bending Radius:	25 mm		

## ENVIRONMENTAL

Operating Temperature Range:	$-55^{\circ}\text{C} < \theta < +70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

## ELECTRICAL

Impedance:	50 $\pm$ 1 $\Omega$			
Operating Frequency Range:	DC ~ 3GHz			
RMS Power (40 $^{\circ}$ C - 2 GHz):	0.52 KW			
Velocity:	83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	$\leq -160$ dBc		
	IM3 at 1800MHz	$\leq -160$ dBc	IM7 at 2100MHz	$\leq -160$ dBc

## RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
0.5	C2377E	230	-32	0.18	-30	0.27	-26	0.33
1	C0867E	315	-32	0.21	-30	0.33	-26	0.37
1.5	C0868E	400	-32	0.26	-30	0.40	-26	0.47
2	C0296E	485	-32	0.33	-30	0.48	-26	0.57
3	C0869E	655	-32	0.43	-30	0.66	-26	0.78
5	C2017E	990	-32	0.67	-30	1.02	-26	1.22