



C2677E-L100 | HYPERCELL

Jumper 1/2SF PE 4.3-10 Male - 4.3-10 Female

GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF PE cable
Connector:	Screw type 4.3-10 male/4.3-10 Female
Assembly:	Inner and outer contact 100% soldered and with molding

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	8 N.m Max.
Minimum Bending Radius:	25 mm

ENVIRONMENTAL

Operating Temperature Range:	-55°C < θ < + 70°C
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 62037, IEC 60529

ELECTRICAL

Impedance:	50 \pm 1 Ω
Operating Frequency Range:	DC ~ 3GHz
RMS Power (40 °C - 2 GHz):	0.5 KW
Velocity:	83%

Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carriers:	IM3 at 900MHz	≤ -161 dBc		
	IM3 at 1800MHz	≤ -161 dBc	IM7 at 2100MHz	≤ -161 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
0.5	C2677E-L50	160	-32	0.26	-30	0.29	-26	0.31
1	C2677E-L100	244	-32	0.31	-30	0.37	-26	0.41
2	C2677E-L200	415	-32	0.42	-30	0.54	-26	0.60
3	C2677E-L300	585	-32	0.53	-30	0.71	-26	0.81
5	C2677E-L500	925	-32	0.75	-30	1.05	-26	1.20

NORMS AND STANDARDS

RECOMMENDATIONS