



## C0270F HYPERCELL

HPL Framework Grounding Kit

### GENERAL CHARACTERISTICS

|                  |  |
|------------------|--|
| Framework Body:  | EPDM + Stainless steel   |
| Grounding Cable: | Copper (0.6m length)   |
| Compatibility:   | Matching with the cable with copper or Aluminium outer conductor |

### MECHANICAL & ENVIRONMENTAL

|                   |       |
|-------------------|-------|
| Color:            | Black |
| Waterproof Index: | IP68  |
| RoHS Compliance:  | Yes   |

### ELECTRICAL

|                            |  |
|----------------------------|--|
| Impact Current Resistance: | Grounding kit is able to bear or endure concussion current level reaching 70KA |
| Contact Resistance:        | $\leq 5 \text{ m}\Omega$   |

## RANGE

| Product number | Type                                     | Approx. weight (g / p) |
|----------------|--|------------------------|
| C0275F         | 1/4XF ( $\varnothing 6.85 \times 600$ )  | 190                    |
| C1113F         | 1/4F ( $\varnothing 6.85 \times 600$ )   | 190                    |
| C0270F         | 3/8XF ( $\varnothing 10.1 \times 600$ )  | 190                    |
| C1114F         | 3/8F ( $\varnothing 10.1 \times 600$ )   | 190                    |
| C0271F         | 1/2F ( $\varnothing 16 \times 600$ )     | 200                    |
| C0272F         | 7/8F ( $\varnothing 27 \times 600$ )     | 215                    |
| C0273F         | 1-1/4F ( $\varnothing 39.5 \times 600$ ) | 245                    |
| C0274F         | 1-5/8F ( $\varnothing 50 \times 600$ )   | 255                    |