



## C0774X HYPERCELL

HPL Single Clamp for Leaky Cable

### GENERAL CHARACTERISTICS

|                          |                        |
|--------------------------|------------------------|
| Part 1:                  | Nylon                  |
| Part 2:                  | Nylon                  |
| Screw (Part 3)           | Galvanized Q235 M8 ×20 |
| Tube Nut (part 4)        | Galvanized Q235 M8 ×L  |
| Expansion Screw (Part 5) | Galvanized Q235 M8 ×70 |

### MECHANICAL & ENVIRONMENTAL

|                        |                            |
|------------------------|----------------------------|
| Color of The Body:     | Black                      |
| Use Temperature Range: | -40 °C < $\theta$ < +85 °C |
| RoHS Compliance:       | Yes                        |
| UV Resistance:         | Yes                        |
| Flame Resistance:      | UL94V-2                    |

# RANGE

| Product number | Type    | Clamp support<br>H(part 1, mm) | Tube nut L (mm) | Approx. weight (g / p) |
|----------------|---------|--------------------------------|-----------------|------------------------|
| C0771X         | 1/2RM   | 50                             | 33              | 120                    |
| C0772X         | 7/8RM   | 50                             | 33              | 126                    |
| C0773X         | 1-1/4RM | 80                             | 66              | 162                    |
| C0774X         | 1-5/8RM | 80                             | 66              | 165                    |