



C1312E | HYPERCELL

Jumper 1/4SF LSOH N Male Elbow - N Male

GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/4SF LSOH cable
Connector:	N male elbow / N male
Assembly:	Inner and outer contact 100% soldered and with thermal shrink tube

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	2.5 N.m Max.
Minimum Bending Radius:	25 mm

ENVIRONMENTAL

Operating Temperature Range:	$-40^{\circ}\text{C} < \theta < +70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

ELECTRICAL

Impedance:	$50 \pm 1\Omega$
Operating Frequency Range:	DC ~ 3GHz
RMS Power (40 °C - 2 GHz):	0.35 KW

Velocity:		83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carriers:		IM3 at 900MHz	≤ -145 dBc		
		IM3 at 1800MHz	≤ -145 dBc	IM7 at 2100MHz	≤ -145 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
1	C1311E	260	-28	0.32	-26	0.49	-24	0.57
2	C1312E	345	-28	0.55	-26	0.79	-24	0.93
2.5	C1301E	385	-28	0.62	-26	0.94	-24	1.11
3.5	C1302E	470	-28	0.81	-26	1.24	-24	1.46

NORMS AND STANDARDS