



C0886E HYPERCELL

Jumper 1/2SF PE N Male - 7/16 Din Female

GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF PE cable
Connector:	N male / 7/16 Din female
Assembly:	Inner and outer contact 100% soldered and with molding

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass		
Material and Finish of Coupling Nut:	Nickel - plated brass		
Material and Finish of Inner Conductor:	Silver - plated bronze		
Coupling Waterproof:	Silicone Rubber O-ring		
Coupling Torque:	N interface	2.5 N.m Max.	
	Din interface	30 N.m Max.	
Minimum Bending Radius:	25 mm		

ENVIRONMENTAL

Operating Temperature Range:	$-55^{\circ}\text{C} < \theta < +70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

ELECTRICAL

Impedance:	50 \pm 1 Ω			
Operating Frequency Range:	DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):	0.52 KW			
Velocity:	83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	≤ -160 dBc		
	IM3 at 1800MHz	≤ -160 dBc	IM7 at 2100MHz	≤ -160 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
0.5	C2364E	245	-32	0.17	-30	0.26	-26	0.31
1	C0705E	330	-32	0.21	-30	0.33	-26	0.37
2	C0637E	500	-32	0.33	-30	0.48	-26	0.57
3	C0886E	670	-32	0.43	-30	0.66	-26	0.78
5	C2021E	1010	-32	0.67	-30	1.02	-26	1.22