
MCD1522-HD

High Density Optical Fibre Mini Cable for blowing into microducts with 12 fibre / tubes

Outdoor cable - Dielectric

From 12 to 288 fibres



Applications

ACOPTIC® is the range of ACOME's optical cables solutions for telecom networks.

The MCD1522-HD range is **high-density Mini-Cables** designed to be blown into Microducts installed for telecom networks (Transport and access networks).

The MCD1522-HD is **designed to be used with small microducts** either on new installation or to upgrade existing installations. This range of cables is blown on short and large distances.


Benefits

- **Density:**
  - up to 288 fibres with 10/12 mm Microducts
- **Convenient:** ACOME's 200µm Optical fibre is fully compatible with G652D, G657A1 and G657A2
- **Efficiency**: Together with the low friction sheath material HDPE, the shape of the cable offers reduced contact surface to its low friction sheath.

Standards

IEC/EN 60793 (fibre)
IEC/EN 60 794-5-10 (cable)

Design



1. **Single Mode fibres with 200 µm diameter**
2. **HD-Tube®** with 12 fibres
3. **Central strength member :** rigid FRP
4. **Watertightness**: Dry water blocking elements
5. Rip Cord
6. **Low friction outer jacket**: HD Polyethylene

Example : 288f — 12f per tube

Storage, packaging & installation

Cable protection on the drum

Cables are delivered with a covering for protection until they are required for installation.

Guidelines access

Guidelines for storage, transportation & cable installation can be found in our ACOPTIC® guide

Cable Implementation sheet available under APC MCD Micro-Loose Tube



This documentation is the exclusive property of ACOME. Any reproduction, copying, extraction, modification, etc., in whole or in part, is strictly forbidden without the prior written authorisation of ACOME. Due to technical evolution, ACOME reserves the right, at any time and without notice, to modify the technical specifications announced for this product and/or to stop the manufacture of it unless contractual commitment. The ACOME mark is a registered trademark.

52 rue du Montparnasse 75014 Paris - France - T. +33 1 42 79 14 00
www.acome.com

MCD1522-HD

MCD1522 Technical Information

Fibre Count	Fibres per Tube	Nb of Tubes + dummy tubes	Nominal Cable Ø in mm	Minimum Inner Ø Duct Size in mm	Maximum Tensile Strength (1) (N)	Crush Resistance N/dm	Minimum Bending radius (mm)	Nominal Weight (kg/km)	Part Number	Carbon Foot-print (2) in (kgCO_2eq/ km cable)
12f	12	1+5	4.2	6	600	500	80	16	H0621B	n/a
24f	12	2+4	4.2	6	600	500	80	16	H0622B	n/a
36f	12	3+3	4.2	6	600	500	80	16	H0623B	n/a
48f	12	4+2	4.2	6	600	500	80	16	H0624B	177.62
60f	12	5+1	4.2	6	600	500	80	16	H0625B	n/a
72f	12	6	4.2	6	600	500	80	17	H0508B	n/a
96f	12	8	4.9	8	900	500	90	25	H0509B(3)	n/a
144f	12	12	6.4	8	900	500	130	37	H0933B(3)	478.05
288f	12	24	7.5	10	1200	500	150	54	H0917A	n/a

(1) fibre elongation ≤ 0,6%
(2) Total carbon footprint over the entire product life cycle, LCA carried out in accordance with the PEP framework (PCR/PSR-0001 ed.4) and the cable-specific rules defined in IEC TR 62839-1:2025 – please contact our teams for further information.
(3) For this item specific lead-time may apply

Temperature Performance	Transport & storage	-40°C/+70°C
	Installation	-10°C/+50°C
	Operation	-30°C/+60°C
Marking		Day Month Year Hour - ACOME MCD1522HD - fibre qty x fibre type - M12 - P/N - metric
Standard Delivery Drum Length		4000m / 6000m

Colour code

Fibre / Tube number	1	2	3	4	5	6	7	8	9	10	11	12
DIN VDE0888	Red	Green	Blue	Yellow	White	Grey	Brown	Violet	Turquoise	Black	Orange	Pink

ACOME selection guide for Microducts

MCD1520 : 12f 250µm / tube
MCD1521-HD : 24f 200µm / tube
MCD1522-HD : 12f 200µm / tube

Microduct Inner-Ø	12-72f	96f	144f	192f	216f	288f	432f	576f
Ø 6	**MCD1522-HD**							
Ø 8	MCD1520	MCD1520 **MCD1522-HD**	MCD1521-HD **MCD1522-HD**	MCD1521HD				
Ø 10	MCD1520	MCD1520	MCD1520 MCD1521-HD **MCD1522-HD**	MCD1520 MCD1521-HD	MCD1520 MCD1521-HD	MCD1521-HD **MCD1522-HD**	MCD1521-HD	
Ø 12			MCD1520	MCD1520	MCD1520	MCD1520 MCD1521-HD **MCD1522-HD**	MCD1521-HD	MCD1521-HD

For other requirements (delivery length, colour code, additional technical information, etc.), please contact us.

This documentation is the exclusive property of ACOME. Any reproduction, copying, extraction, modification, etc., in whole or in part, is strictly forbidden without the prior written authorisation of ACOME. Due to technical evolution, ACOME reserves the right, at any time and without notice, to modify the technical specifications announced for this product and/or to stop the manufacture of it unless contractual commitment.. The ACOME mark is a registered trademark.

52 rue du Montparnasse 75014 Paris - France - T. +33 1 42 79 14 00
www.acome.com